



Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India
P : 9210 903 903, +91 129 4272727, 93111 24302 E : info@prestogroup.com

• Faridabad • Sonapat • Kolkata • Mumbai • Pune • Ahmedabad
• Chennai • Bangalore • Hyderabad

www.prestogroup.com



Model No. : PRBT - 0201


The instrument is designed based on the balling method, and the primary adhesive property of adhesive tapes could be obtained by observing adhesive effect occurred immediately after rolling ball and adhesive specimen come into contact.

Application : Adhesives: Including various adhesives, e.g. pressure-sensitive tapes, medical patches, adhesive labels and protection films.

- Based on the rolling ball method and test the instant adhesive property of specimens.
- Testing steel balls are designed strictly according to national standards, which ensure the accuracy of test data.
- Angle of inclination could be freely to meet customer test requirements.
- Spring lever designed to release the ball with minimal user interference.
- Simple loading of the ball for quick and easy operation.
- CNC machined inclined trough, engineered for a smooth and accurate test

Standards

ASTM D3121





Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India

P : 9210 903 903, +91 129 4272727, 93111 24302 E : info@prestogroup.com

• Faridabad • Sonapat • Kolkata • Mumbai • Pune • Ahmedabad
• Chennai • Bangalore • Hyderabad

www.prestogroup.com



Key Specifications:

Angle Range	21° 30'
Test table area width	50 mm (Glass surface)
Standard steel Ball	11.1 mm
Range of Scale	300 mm
Scale Least count	1 mm

Highlights:

Material	Mild Steel
Finish	Powder coated Havel Gray & Blue combination finish and bright chrome / zinc plating for corrosion resistant finish
Steel Ball	1 no.
Ball Dropping Mechanism	Spring operated
Dimensions	655 x 100 x 200 mm

The result is divided in 3 zones.

- 1) 0-100 mm is High Tack Zone.
- 2) 100 – 200 mm is Medium Tack Zone.
- 3) 200 – 300 mm is Low Tack Zone. Based on your application

Optional :

- Steel Ball other sizes upto 1 inch are also available.

Thank you customers for choosing us as your partners in growth !



*All the above logos are the sole property of their respective owners and are used purely for depiction purposes only.

OUR OTHER PRODUCTS :-

Box Compression Tester	Scuff Resistance Tester	Tensile Tester Digital	Spectrocolorimeter	Cobb Sizing Tester	Digital GSM Balance

Head Office : Presto Stantest Private Limited

I-42, DLF Industrial Area Phase-I, Delhi Mathura Road, Faridabad 121003, Haryana, India

P : +91 129 4272727 E : info@prestogroup.com

Branches :

Mumbai
503-504B, Fair link Centre, Opp. Fame Adlab
Behind Mongini's Off Link Road
Andheri (West), Mumbai 400058
P : +91 022 42957052, 42957053
E : west@prestogroup.com

Kolkata
93, 3rd Floor, Karnani Estate
209, A.J.C. Bose Road
Kolkata-700017, West Bengal
P : +91 033 40612012
E : east@prestogroup.com

Chennai
A-3, First Floor, Sri Sathya Sai Building
755, Poonamallee High Road, Kilpauk
Chennai- 600 010. Tamil Nadu
P : +91 044 43865260, 43838372
E : south@prestogroup.com

www.prestogroup.com

