

Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P: 9210 903 903, +91 129 4272727, S 93111 24302 E: info@prestogroup.com



• Faridabad • Sonipat • Kolkata • Mumbai • Pune • Ahmedabad • Chennai • Bangalore • Hyderabad


www.prestogroup.com

Cone Crush Tester - Digital




Model No. PCCT - 100


Cone Crush Tester Digital is a consistent tool to measure the crush strength of cardboard cone, Paper tubes, bobbins & core packaging material. It is based on Radial Crush method. It is designed in such a manner that gradually increasing force is generated & applied on 66% of the surface of the carrier. The sharp collapsing point can be easily detected and a suitable reading can be taken.



Top View



Front View



Side View



Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P: 9210 903 903, +91 129 4272727,
93111 24302 E: info@prestogroup.com



· Chennai · Bangalore · Hyderabad www.prestogroup.com



Collapsing strength tester is designed in such a manner that gradually increasing force is generated & applied on the surface of the carriers. The sharp collapsing point can be easily detected with the help of a Loadcell and Microprocessor based digital indicator.

- Microprocessor based display for accurate test results
- Display for compression strength of test specimen
- Highly accurate test results under compression force
- Strong gripping clamps.
- **Bright LED display**
- Inbuilt calibration facility
- Feather touch controls

*For Paper Tubes / Cores used as Winding Medium / Carrier, Radial Crush Test is performed.

Cone / Core Crush Tester reveals the crushing resistance in terms of Kg/Unit length.

Optional Features:

- Computerised model also available
- Digital model with printer facility also available.

Key Specifications:

Load CellCapacity	500 Kgf
Display	• LED (Digital)
Accuracy	$\pm 2\%$ at full load (with master load)
Least Count/Resolution	0.01 Kgf
Power	220V, Single phase, 50 Hz
Test Speed	12.5 ± 2.5 mm/min

Highlights:

Safety Switch	Upward & Downward Limit Switches
Material	Mild Steel
Finish	Powder coated Havel Grey & Blue combination finish and bright chrome / zinc plating for corrosion resistant finish
Dimensions	600x500x863 mm

Thank you customers for choosing us as your partners in growth!





























*All the above logos are the sole property of their respective owners and are used purely for depiction purposes only.

OUR OTHER PRODUCTS:-















Tensile Tester Digital

Spectrocolorimeter

Cobb Sizing Tester

Digital GSM Balance